# 030-0825 Flush Mounted Paddle Handle With Inside Release





This flush paddle was designed for medium to heavy-duty on-highway vehicle entrance doors and features robust construction and an integrated inside release lever that reduces the need for a separate inside release.

## **DESIGNED FOR:**

- Off-highway applications--construction, mining, forestry and agricultural
- On-highway--emergency vehicles not requiring FMVSS 206 (ECE R11) standards

#### **Global Locations:**

Tri*Mark* Corporation 500 Bailey Avenue P.O. Box 350 New Hampton, Iowa 50659 United States Tel: 641-394-3188 Fax: 641-394-2392 1-800-447-0343

www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058

www.trimarkcn.com

TriMark

TriMark Corporation

TriMark. Interactive. Product. Selector



# 030-0825

#### FEATURES/BENEFITS:

- Mounts in doors requiring latch location remote from activating handle
- Can be used with both cutouts shown in drawing
- Inside release lever eliminates much of the linkage typically required with conventional inside handle
- Operator can exit even if the door is locked from the outside

### AVAILABLE:

- In right or left hand configurations
- Non-locking or locking--keyed alike with shuttered keyway
- Optional pivot plates available for your particular application

For more information visit www.trimarkcorp.com

#### **MATERIAL:**

- Housing and paddle: sturdy die cast zinc alloy
- Pivot components: zinc plated, mild steel
- Bushing for paddle axle and thrust washers for pivot plate: Nylon 6/6

#### FINISH:

• Housing and paddle can be finished in your choice of black powder coat or buffed copper-nickelchrome

#### **INSTALLATION:**

• Easily installed with (2) 1/4-20 UNC mounting screws and brackets (screws and brackets are supplied)

**CAUTION:** Product does not meet the locking requirements for FMVSS 206 (ECE R11).

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

