

# 040-0100 Push Button Handle



### **DESIGNED FOR:**

- Off-highway applications -- construction, mining, agricultural
- Outside latch release
- Entry assist

### **FEATURES/BENEFITS:**

- Frictionless push button seal
- Flow through self-cleaning design
- Readily adaptable to a variety of door thickness with a 1/4" diameter capscrew

### **Global Locations:**

**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
www.trimarkcorp.com

**TriMark Europe**  
Cedar Court  
Walker road  
Bardon Hill  
Coalville LE67 1TU  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
www.trimarkeu.com

**TriMark (Xuzhou)**  
Building A5 Jingwu Road  
Xuzhou Economic  
Development Zone  
Xuzhou, Jiangsu  
221004 PR China  
Tel: +86 516 8773 0018  
Fax: +86 516 8773 0058  
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation

**MATERIAL:**

- Die cast zinc alloy

**FINISH:**

- Black powder coated
- Copper-nickel-chrome

**INSTALLATION:**

- Installed with (3) M6x1 bolts
- Spacers are available to mount the handle on a flat surface

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

