030-0900 Motor Home Entrance Door Hardware With Dead Bolt



DESIGNED FOR:

- Motor home entrance doors with thickness of 1-1/2” (38.1mm), 1-5/8” (41mm) or 1-7/8” (47.6mm)
- Fifth-wheel trailers and motor homes
- Applications requiring resistance to water and dirt infiltration
- Door seal pressures of 25 lbs. (11 kg) or less for ease of function and maximum life (not to exceed 50 lbs. [23 kg])
- Right hand applications
- Door weights up to 75 lbs. (34 kg)

FEATURES/BENEFITS:

- Automotive style latch mechanism
- Smooth opening/closing action
- Paddle can be locked before door is shut
- Paddle is rigid when locked
- Comfortable finger access
- New inside handle design facilitates ergonomic function and modern styling
- Adaptable for power door lock actuator
- Built-in dead bolt eliminates the need for an add-on residential type dead bolt
- Dead bolt locks into the fully extended position for true dead bolt functioning

Bookmark TriMark at TriMark Interactive Product Selector
www.trimarkcorp.com

TriMark®

500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

A3057 ISO 9001:2000
TriMark Corporation

TriMark Europe, Ltd.
Cedar Court
Walker Road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44 (0)1530 512460
Fax: +44 (0)1530 512461
www.trimarkeu.com

A14636 ISO 14001:2004
A3057 ISO 9001:2000
TriMark Europe Limited

030-0900 Motor Home Entrance Door Hardware With Dead Bolt

AVAILABLE:

- Master keyed passage lock key cylinder. Non-master keyed dead bolt
- Gasket (not included)
- KeyOne™ Plus
- Standard or extended length deadbolt
- Sandwich mounting is available for door thicknesses of 1.500 (38.1mm), 1.614 (41mm) or 1.875 (47.6mm)

MATERIAL:

- Housing, inside plates, paddles, and certain lock actuating components: die cast zinc alloy
- Internal latch components: heat treated, smooth edge stamped steel
- Springs: non-corrosive stainless steel
- Case halves: high strength steel

FINISH:

- Black powder coated
- Chrome plated
- Interior release: low gloss black or white powder coat

KeyOne™ Plus is available. The KeyOne™ system allows the operation of multiple on board locking hardware with a single key. KeyOne™ Plus features include a reversible key for ease of operation and a larger body diameter for enhanced security. Please call for more information.

INSTALLATION:

- #8-32 UNC mounting screws (not included). Recommended torque 13 in./lbs.
- Sandwich mount installation does not require any linkage rods

USE WITH:

- Please refer to our website for related products that are compatible for use with this product

Meets FMVSS 206 load requirements and may be used in FMVSS 206 applications pending TriMark application approval.

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

U.S. Patent No. 4,736,972 & 5,127,686
Canadian Patent No. 2045831
Design Patent No. D529,367







