

030-2300X  
Wedge Paddle  
Handle



This flush mounted paddle handle is designed specifically for medium to heavy-duty off-highway vehicle entrance doors that require remote actuation. It is retrofittable with similar excavator paddle handles and offers robust construction for a very cost effective price.

**FEATURES/BENEFITS:**

- Off-highway construction equipment applications
- Doors requiring latch location remote from actuating handle
- Door thickness of 55mm or greater
- Comfortable finger access
- Adaptable for power door lock actuation
- Molded gasket for flange of housing provides resistance to water infiltration



[www.trimarkcorp.com](http://www.trimarkcorp.com)

**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

**TriMark Europe**  
Cedar Court  
Walker Road  
Bardon Hill  
Coalville LE67 1TU  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
[www.trimarkeu.com](http://www.trimarkeu.com)

**AVAILABLE:**

- Lock can be keyed to match other TriMark door products with KeyOne Plus for a single-key system, keyed alike or provided non-locking
- Choice of locking functions; locked rigid within the paddle or remote free-float locking to connect with latch/linkage
- Right hand version (shown)



### ***INSTALLATION:***

- Easy to install with (3) M6 X 1 mounting screws (not included)

**For more information visit  
[www.trimarkcorp.com](http://www.trimarkcorp.com)**

**MATERIAL:**

- Sturdy die cast zinc alloy paddle and housing
- Pivot plate, lock cam and paddle axle: mild steel


***FINISH:***

- Black powder coated housing and paddle
- Zinc plated clear chromate steel components

Free-float locking version meets recognized standards for on-highway vehicles for the locking function.



Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

REVISION	ECO	ECO BY	DESCRIPTION
A	PRE- LISE	XXX DD/MM/YY	CREATED



REVISION	ECO	ECO
A	PRE- RLSE	XX DD/MM

## ENGINEERING



**CAUTION:** The free-floating version does not meet the locking requirements for FMVSS 206.