030-7150 Plastic Rectangular Paddle Handle





This 030-7150 Plastic Rectangular Paddle Handle is designed for use on personnel and compartment doors for light to medium duty, on or off-road applications. The paddle rotation drives a plunger output which allows for a direct latch release providing a compact and low-cost access solution.

DESIGNED FOR:

• Use in a direct latch release application or in conjunction with a bell crank or single point remote actuation



Global Locations:

1-800-447-0343

www.trimarkcorp.com

TriMark Corporation 500 Bailey Avenue P.O. Box 350 New Hampton, Iowa 50659 United States Tel: 641-394-3188 Fax: 641-394-2392

TriMark Europe Cedar Court Walker road Bardon Hill Coalville LE67 1TU United Kingdom Tel: +44(0)1530 512460 Fax: +44(0)1530 512461 www.trimarkeu.com

TriMark (Xuzhou) Building A5 Jingwu Road Xuzhou Economic Development Zone Xuzhou, Jiangsu 221004 PR China Tel: +86 516 8773 0018

Fax: +86 516 8773 0058 www.trimarkcn.com







030-7150 Plastic Rectangular Paddle Handle

FEATURES/BENEFITS:

- Non-handed configuration allows for universal applications
- Interior or exterior applications
- The handle is rigid when locked
- Readily adaptable to a variety of doors with an adjustable bolt and nut

AVAILABLE:

 Lock can be keyed to match other TriMark door products with KeyOne Plus™ for a single-key system, keyed alike or provided non-locking

♣TriMark

KEY

• With gasket for maximum water resistance

MATERIAL:

- Handle, paddle and actuator: Engineered plastic withstands corrosion and UV exposure
- Spring: Non-corrosive stainless steel
- Lock Cam Fastener, drive screw and nut: Steel

FINISH

- Standard black color
- Zinc plated clear chromate steel components

INSTALLATION:

- Easy installation with (3) #10-14 high performance thread forming fasteners (not included). Mounting torque not to exceed 40 in-lbs. (4.52 N-m)
- Mounting bracket (not included)

CAUTION: Product does not meet the locking requirements for FMVSS 206 (ECE R11).

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit www.trimarkcorp.com







