

040-0550
163mm Push
Button Handle



This handle was specifically designed for off-highway vehicle applications that require a surface mounted exterior push button handle with 163mm mounting pattern. It is retrofittable with most European push button handles and offers robust construction, ergonomic function and styling for a very cost effective price.

DESIGNED FOR:

- On or off-highway vehicle applications
- Push button handles requiring 163mm mounting

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation

FEATURES/BENEFITS:

- Frictionless push button seal
- Flow through self-cleaning design
- Readily adaptable to a variety of door thicknesses with an adjustable bolt and nut (option -CC)
- Full gloved hand clearance
- .625" (15.88mm) button travel
- Exterior push button surface mount
- Button locks rigid when locked
- Snap-in retainer side plates allow for alternate color and/or customer branding
- Easy to operate (ergonomics)

AVAILABLE:

- Can be keyed alike with most single and reversible key systems
- With adjustable bolt
- In locking or non-locking configurations

MATERIAL:

- Handle: glass reinforced nylon
- Brass threaded inserts

INSTALLATION:

- Installed with (2) M8 x1.25 bolts (not included)
- Mounts against glass with only 2 holes
- Recommended mounting fastener torque to be 6.7-7.9 N-m (59-70 lbf-in)

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit
www.trimarkcorp.com

