

060-0460
EZ Access Baggage
Door Lock



DESIGNED FOR:

- Recreational vehicle baggage doors and engine compartments

FEATURES/BENEFITS:

- Offers lower operating efforts and a more forgiving assembly
- Ample finger clearance
- Paddle can be locked before the door is shut (slam action)
- Updated styling
- Improved plunger design
- Increased mechanical advantage to allow for lower operating efforts
- Available in single or three point actuation for latching versatility

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector






- Paddle and housing: powder coat in various colors
- Steel components: zinc coat with clear chromate

- Housing and paddle: die cast zinc
- Pivot plate, axles, pivot arm: steel
- Plunger bolt: plastic or die cast zinc

- Locking or non-locking
- Keyed alike
- Wide variety of mounting bracket options available for various applications
- KeyOne™ Plus
- Multi-point actuation or single point
- Zinc or plastic plunger



Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

Technical drawings of the 22317-XXX LED light assembly showing front, side, and rear views with dimensions in inches and millimeters.

Front View Dimensions:

- Width: 4.750 [120.65]
- Height: 5.250 [133.35]
- Bottom Mounting Hole Spacing: .500 [12.69]

Side View Dimensions:

- Top Mounting Flange Width: 1.580 [40.13]
- Bottom Mounting Flange Width: .600 [15.24]
- Bottom Mounting Flange Thickness: 1.260 [32]
- Internal Mounting Flange Width: .639 [16.23]
- Internal Mounting Flange Thickness: .625 [15.88]

Rear View Dimensions:

- Top Mounting Flange Width: 2.893 [73.48]
- Top Mounting Flange Thickness: .840 [21.32]
- Top Mounting Flange Hole Spacing: .741 [18.81]
- Top Mounting Flange Hole Diameter: 3xØ.108 [5.03]
- Top Mounting Flange Hole Position: .391 [9.94]
- Top Mounting Flange Hole Diameter: 2.353 [59.77]
- Top Mounting Flange Hole Position: 1.000 [25.41]
- Top Mounting Flange Hole Diameter: .741 [18.81]
- Top Mounting Flange Hole Position: 1.683 [42.75]
- Top Mounting Flange Hole Position: .735 [18.67]

Part Number: 22317-XXX

For more information, visit: www.ledlighting.com