

060-0600
Motor Home Entrance
Door Hardware
060-0650 Dead Bolt Option



DESIGNED FOR:

- Motor home entrance doors with thickness of 1.390" to 1.600". (Different inside plates are required to facilitate range of door thicknesses. Please identify when inquiring.)
- Fifth-wheel trailers, pull-type trailers and slide-in campers
- Doors requiring resistance to water and dirt infiltration
- Universal applications--either right or left handed

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation



060-0600 Motor Home Entrance Door Hardware 060-0650 Dead Bolt Option

FEATURES/BENEFITS:

- Paddle can be locked before door is shut
- Paddle is rigid when locked
- Automotive styling
- Comfortable finger access
- Inside assist for easy closing
- Serviceable shuttered key cylinder
- Built-in dead bolt eliminates the need for an add-on residential type dead bolt
- Dead bolt locks into the fully extended position for true dead bolt functioning (060-0650)


AVAILABLE:

- With optional built-in dead bolt (060-0650)
- Master keyed paddle key cylinder. Non-master keyed dead bolt

MATERIAL:

- Housing, inside plates, paddles, plunger bolt and certain lock actuating components: die cast zinc alloy
- Strike plate: heat treated and zinc plated steel

For more information visit
www.trimarkcorp.com





060-0600 Motor Home Entrance Door Hardware 060-0650 Dead Bolt Option

FINISH:

- Black powder coated
- Copper-nickel-chrome plated

INSTALLATION

- #10-24 UNC mounting screws (not included).
Recommended torque 10 in./lbs. (1.1 N-m) 1/4-20
UNC grade 5-type fasteners for strike plate
installation recommended
- Supplied with gasket already applied under recess in
housing flange
- Sandwich mount installation does not require any
linkage rods

Meets FMVSS 206 load requirements and may be
used in FMVSS 206 applications pending TriMark
application approval.

Individual part dimensions are for reference only.
Refer to individual part drawings for complete
dimensions, specifications, and installation
procedures. Engineering assistance and application
drawings are available.

