

130-7200 Door Hold-Open



This door hold-open is designed for light to medium duty agricultural, construction or other equipment personnel doors that need to be held in an open position. Any application where it is desirable to hold or retain a hinged door in an open position.

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Unit 3 Sence Court
Bardon Hill
Coalville
Leicestershire LE67 1GZ
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation



TriMark Corporation

FEATURES/BENEFITS:

- Simple, easy to use
- Rotating knob/pin latch
- Engineered to withstand vibration, shock, dust, dirt and moisture
- Ergonomic knob design
- Rotating knob allows for the door to be released from the open position from the ground level
- Durability in tough applications
- Easily adaptable to a wide variety of door/cab configurations

AVAILABLE:

- Single release pin latch or remote release version

For more information visit
www.trimarkcorp.com

MATERIAL/FINISH:

- Glass reinforced nylon - black
- Chromed steel latching pin
- Internal components: Zinc plated steel

INSTALLATION:

- Easy to install, can be mounted on glass or steel doors
- (1) Shouldered hat nut and large rubber O-ring (included)
- Recommended mounting fastener torque on strike sub-assembly to be 6.7 to 7.9 N-m (59 to 70 in. lbs.)

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

Caution: Door hold-open is not designed to secure a door in the closed position and does not comply with FMVSS 206 (ECE R11)

