



210-7100 Hinge  
Assembly - Aluminum



This aluminum hinge is designed for light-duty off-highway vehicle applications on storage compartments or hinged windows.



**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

**TriMark Europe**  
Cedar Court  
Walker Road  
Bardon Hill  
Coalville LE67 1TU  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
[www.trimarkeu.com](http://www.trimarkeu.com)

**TriMark (Xuzhou)**  
Building A5 Jinwu Road  
Xuzhou Economic  
Development Zone  
Xuzhou, Jiangsu  
221004 PR China  
Tel: +86 516 8773 0018  
Fax: +86 516 8773 0058  
[www.trimarkcn.com](http://www.trimarkcn.com)

**FEATURES/BENEFITS:**

- Designed to be used vertically mounted with same type of fixing at both ends
- Mounting configurations (2) M8 bolt, 76mm (3.00") mounting pattern

**MATERIAL/FINISH:**

- Die cast aluminum material
- Black or grey powder coated

**INSTALLATION:**

- Installs with either suitable M8 fixing bolts or mushroom caps for glass mounting (not included)
- Recommended mounting fastener torque to be 6.7 - 7.9 N-m (59 to 70 in-lbs.)

Individual part dimensions are for reference only. Refer to individual part dimensions for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

**All dimensions are for reference only. For more information visit [www.trimarkcorp.com](http://www.trimarkcorp.com)**

