

# 010-1000 Rotating Lever Handle



These robust exterior and interior door handles are fabricated from high strength plate steel and feature modular attach/quick detach drive details and offer 1000 hour Cass protection with a soft touch coating.

**DESIGNED FOR:**

- Entrance and rear door applications for heavy-duty vehicles
- Interior and exterior applications
- Medium to heavy duty doors of 23-455 kg (50-1000 lbs.)



**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
www.trimarkcorp.com



**TriMark Europe**  
Cedar Court  
Walker Road  
Bardon Hill  
Coalville LE67 1TU  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
www.trimarkeu.com



**FEATURES/BENEFITS:**

- Heavy duty construction

**AVAILABLE:**

- A variety of sizes and forms available
- Customization features available: Please inquire
  - ◆ Length and forming of handle
  - ◆ Handle materials

**MATERIAL:**

- Standard — high strength steel construction
- Available with advanced lightweight aluminum alloy

**FINISH:**

- Standard low gloss black powder coated
- Mil-Spec soft grip nylon coated handle
- 1000 hour corrosion protection
- Optional finishes available including: Black Magni™ coating, Tan/Olive CARC paint and Tan/Olive powder coating

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

**U.S. Design Patents: D596,917 / D615,383 / D615,841**



For more information visit  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

