

## 040-7200 Push Button Handle—Flat Style



This push button handle is designed for off-highway vehicle applications that require a surface mounted exterior push button handle.

**FEATURES/BENEFITS:**

- 2 or 3 bolt 120 mounting
- Readily adaptable to a variety of door thickness using various cams
- Suitable for mounting to glass, steel and composite surfaces
- 12mm button travel
- Incorporates push button thumb shield
- Easy to operate

**TriMark Europe**  
Cedar Court  
Walker Road  
Bardon Hill  
Coalville LE67 1TU  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
[www.trimarkeu.com](http://www.trimarkeu.com)

**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, IA 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

**TriMark Xuzhou**  
Building A5 Jinwu Road  
Xuzhou Economic  
Development Zone  
Xuzhou, Jiangsu  
221004 PR China  
Tel: +86 516 8773 0018  
Fax: +86 516 8773 0058  
[www.trimarkcn.com](http://www.trimarkcn.com)

# 040-7100 Push Button Handle—Economy

## AVAILABLE:

- Can be keyed alike with most single and reversible key systems or non-locking configurations
- Free-float locking
- Variety of cam options

## MATERIAL:

- Handle/Button: Glass reinforced nylon
- Brass threaded M6 inserts

## INSTALLATION:

- Installed with 2 or 3 M6 X 1.0 bolts (not included)
- Mounts against glass with only 2 holes
- Available with mounting gaskets
- Recommended mounting fastener torque to be 6-8 N-m (50-59 lbf-in)

All dimensions are for reference only. For more information visit [www.trimarkcorp.com](http://www.trimarkcorp.com)

