030-2650 Motor Home Entrance Door Hardware—Rotary







Designed for motor home and fifth wheel trailer entrance doors, this new product is a redesign of our 030-1000/030-1050 Motor Home Entrance Door Hardware. It features easy installation through sandwich mounting, a reliable direct release rotary latch which is compliant to FMVSS 206 (ECE R11), a builtin deadbolt for additional security and is power lockable.

DESIGNED FOR:

- Motor home entrance doors with thickness of 1.390" (35.3mm) to 1.78" (45.2mm) (Different inside plates are required to facilitate range of door thicknesses. Please identify when inquiring.)
- Fifth-wheel trailers, pull-type trailers and slide-in campers
- Door seal pressures of 40 lbs. or less for ease of function and maximum life
- Right hand applications
- Door requiring resistance to water and dirt infiltration
- Use with TriMark 070-0100 Striker Bolt

Global Locations:

1-800-447-0343

www.trimarkcorp.com

TriMark Corporation 500 Bailey Avenue P.O. Box 350 New Hampton, Iowa 50659 **United States** Tel: 641-394-3188 Fax: 641-394-2392

TriMark Europe Cedar Court Walker road Bardon Hill Coalville LE67 1TU United Kingdom Tel: +44(0)1530 512460 Fax: +44(0)1530 512461 www.trimarkeu.com

TriMark (Xuzhou) Building A5 Jingwu Road Xuzhou Economic Development Zone Xuzhou, Jiangsu 221004 PR China Tel: +86 516 8773 0018 Fax: +86 516 8773 0058

www.trimarkcn.com

TriMark TriMark Corporation

TriMark. Interactive. Product. Selector



FEATURES/BENEFITS:

- Inside release is low profile .940" (23.9mm) to allow for close-fitting screen doors
- Paddle can be locked before door is shut
- Paddle is rigid when locked
- Automotive styling
- Comfortable finger access
- · Inside assist with open bail for easy closing
- Can be keyed to match other Tri Mark door products with KeyOne™ Plus for a single-key system, keyed alike or provided non-locking




030-2650 Motor Home Entrance Door Hardware—Rotary

- Built-in deadbolt eliminates the need for add-on residential type deadbolt (deadbolt option)
- Deadbolt locks into the fully extended position for true deadbolt functioning (deadbolt option)
- Ability to be used with power actuation for locking (deadbolt option)
- Deadbolt cylinder non-removable when locked for added security

AVAILABLE:

- With optional built-in deadbolt
- Master keyed paddle key cylinder
- Without key cylinders for matching entire vehicle cylinders after installation






MATERIAL:

 Housing, inside plates, handles, plunger bolt, deabolt, locking components including lock knobs: die cast zinc alloy

FINISH:

- Black powder coated
- · Copper-nickel-chrome plated
- Other finishes available upon request

For more information visit www.trimarkcorp.com




030-2650 Motor Home Entrance Door Hardware—Rotary

INSTALLATION

- (3) #10-24 mounting screws (not included). Recommended torque 10 in-lbs (1.1 N-m)
- Supplied with gaskets already installed
- Sandwich mount installation does not require any linkage rods
- Power actuators, power actuation mounting brackets and rods are available for optional power actuation of locks. Please inquire.

U.S. Patent No. 8,733,139 U.S. Design Patent No. D674,678 / D676,304

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.



CAUTION: Applications of this system may fall within the requirements of FMVSS 206 (ECE R11) and SAE J839 safety standards. These safety related requirements are dependent on door application, e.g. front and rear hinged doors, sliding doors, or hinged upward swinging doors. The entire door hardware system must be included in the design/analysis process: latch, handle, lock mechanism, cables/rods/ linkages, fasteners, hinges, etc. This ensures compatibility of all components within the hardware system. If FMVSS 206 (ECE R11) is a requirement, then all of the components within the door system must comply with strength, inertia and locking requirements as specified within the Standard. Note that this product complies with FMVSS 206 (ECE R11) when tested in accordance with SAE J839 and that this system meets FMVSS 206 (ECE R11) load and locking requirements and may be used in FMVSS 206 (ECE R11) applications pending TriMark application approval.