

060-7100  
Plunger Latch - Low  
Profile L-Handle



Designed for compartment and access doors where low cost slam action latching with L-handle actuation is desired. It features a robust zinc die cast plunger bolt for durability.



TriMark. Interactive. Product. Selector

**Global Locations:**

**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
www.trimarkcorp.com

**TriMark Europe**  
Cedar Court  
Walker road  
Bardon Hill  
Coalville LE67 1TU  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
www.trimarkeu.com

**TriMark (Xuzhou)**  
Building A5 Jingwu Road  
Xuzhou Economic  
Development Zone  
Xuzhou, Jiangsu  
221004 PR China  
Tel: +86 516 8773 0018  
Fax: +86 516 8773 0058  
www.trimarkcn.com



TriMark



TriMark Corporation

**FEATURES/BENEFITS:**

- Various handle styles
- Easy to install
- Accommodates door thickness from 25mm to 50mm (1.00-2.00")
- Non-handed

**AVAILABLE:**

- Several options are available to suit a variety of applications

**MATERIAL**

- Sturdy zinc die cast alloy housing and plunger bolt components

**FINISH:**

- Standard black or silver powder coated
- Other color options available upon request

**INSTALLATION:**

- Easy to install, (4) M5 fixing screws available, not to exceed 6 N-m (50 in-lbs)
- Various base plates available (spacer)

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

