

030-7100
Recessed Paddle Handle



Recessed zinc die cast paddle handle suitable for entrance doors. Robust design that provides long term durability and benefits from TriMark's KeyOne Plus lock system.

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation

FEATURES/BENEFITS:

- Non-handed style can be used in various orientations
- With mounting gaskets
- KeyOne™ Plus allowing for single keying option with variety of key coding available
- Can be used with a wide variety of available interior latch mechanisms
- Accommodates door thickness from 25mm (.98") to 50mm (1.97")

AVAILABLE:

- Lock can be keyed to match other TriMark door products with KeyOne™ Plus for a single-key system, keyed alike or provided non-locking
- Several options are available to suit a wide variety of applications

MATERIAL:

- Sturdy zinc die cast alloy housing and paddle
- Actuator: Glass filled nylon or zinc die cast



FINISH:

- Standard black or silver powder-coated. Other color options available upon request

INSTALLATION:

- Easy to install, (3) 5mm fixing screws (not included), Recommended mounting fastener torque not to exceed 6 N-m (50 lbs-in).
- Various base plates available

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

Caution: Product does not meet the locking requirements for FMVSS 206 (ECE R11).

For more information visit
www.trimarkcorp.com

