

040-7100  
Push Button  
Handle - Economy



This exterior push button handle is designed for off-highway vehicle applications that require a surface mounted exterior push button handle

**Global Locations:**

**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
www.trimarkcorp.com

**TriMark Europe**  
Cedar Court  
Walker road  
Bardon Hill  
Coalville LE67 1TU  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
www.trimarkeu.com

**TriMark (Xuzhou)**  
Building A5 Jingwu Road  
Xuzhou Economic  
Development Zone  
Xuzhou, Jiangsu  
221004 PR China  
Tel: +86 516 8773 0018  
Fax: +86 516 8773 0058  
www.trimarkcn.com



TriMark. Interactive. Product. Selector



**FEATURES/BENEFITS:**

- (2) bolt 120mm (4.72") mounting
- Readily adaptable to a variety of door thickness using various cams
- Suitable for mounting to glass, steel and composite surfaces
- 12mm (.47") button travel
- Easy to operate

**AVAILABLE:**

- Can be keyed alike with most single and reversible key systems or non-locking configurations
- Locked rigid or free-floating versions
- Variety of cam options

**MATERIAL/FINISH:**

- Handle/Button: Glass reinforced nylon
- Brass threaded M6 inserts

**INSTALLATION:**

- Installed with (2) M6 x 1.0 bolts (not included)
- Mounts against glass with only two holes
- Available with mounting gaskets
- Recommended mounting fastener torque to be 6-8 N-m (50-59 lbf-in)

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

**Caution:** Product does not meet the locking requirements for FMVSS 206 (ECE R11).

For more information visit  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

