

060-0100 Plunger Bolt



This plunger bolt was designed for lightweight compartment and access doors where low cost slam action latching with L-handle actuation is desired. It features a robust steel plunger bolt for durability and a base mount that allows for ease of installation.

FEATURES/BENEFITS:

- Minimal door seal pressures
- Easily installed using your choice of mounting fasteners (not included)
- Slotted mounting holes for easy adjustment (mounting surface must be completely flat)

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation

USE WITH:

- Please refer to our website for related products that are compatible for use with this product

AVAILABLE:

- In left or right hand configurations (right hand shown)
- 90° or 20° orientation of 5/16" (8.1mm) square drive bar opening

FINISH:

- Mill - unplated
- Zinc plated
- Black powder coated

MATERIAL:

- Housing: Die cast zinc alloy
- Plunger bolt: Powder metal/steel
- Back Plate: Zinc plated steel

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit
www.trimarkcorp.com

