

060-7200
Heavy Duty Plunger
Latch - Large L-Handle



Designed for compartment and access doors where low cost slam action latching with L-handle actuation is desired. It features a robust zinc die cast plunger bolt for durability.

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



FEATURES/BENEFITS:

- Various handle styles
- Easy to install
- Accommodates door thickness from 25mm to 50mm (1.00-2.00")
- Non-handed

AVAILABLE:

- Several options are available to suit a variety of applications
- Left and right hand variants (handle rotation)

MATERIAL

- Sturdy zinc die cast alloy housing
- Zinc die cast alloy plunger bolt with steel reinforcement plate

FINISH:

- Standard black or silver powder coated
- Other color options available upon request

INSTALLATION:

- Easy to install, (4) M5 fixing screws available, not to exceed 6 N-m (50 in-lbs)
- Various base plates available (spacer)

Individual part dimensions are for reference only.

Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit
www.trimarkcorp.com

