

550-0100 Compact Style Power Lock Actuator



TriMark's new Power Lock Actuator has been tested and validated to meet stringent performance requirements thus insuring a long life of trouble free operation.

DESIGNED FOR:

- TriMark handles and latches equipped to accept a power lock actuator that provides a push/pull function and a clutch that allows for manual override with a key

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation

FEATURES/BENEFITS:

- Reliable and durable to high cycle counts in various environmental extremes
- High impact case design
- Long travel distance - .83" (21mm)
- Each actuator is tested to 10.0 lbs./44.5N - maximum output force is 13.5 lbs./60N. It is recommended that a minimum load of 2.5 lbs./11N be applied in the application for maximum product life.
- Motor is equipped with 12V thermal protection for excessive heating due to extreme usage such as rapid, frequent operations or sustained activation, which can cause premature motor failing or motor seizing
- Motor varistor for electrical transient noise reduction
- Actuator is equipped with a clutch mechanism for soft starts/stops and allows for manual override with key
- Includes a rotatable/detachable tip for ease of application
- 20 gauge, UL 1007 compliant

AVAILABLE:

- Wiring options: blunt ends, bullet connectors, spade or Delphi connectors (please inquire)
- Possible customization available to include special connectors, custom wire length and kitting options. Please contact TriMark for more information.

INSTALLATION:

- TriMark power actuators are easy to install either by integrating or mounting directly into available TriMark latches or handles
- 12 volt supply (9-16 VDC)
- Each actuator can draw up to 4.0A (nominal) of current - proper sized and located circuit protection is required at triggering device (switch/relay) that controls the actuator

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

U.S. Patent No. 10,087,662

For more information visit
www.trimarkcorp.com

